



THE COMBI SYSTEM FOR GREASE AND OIL

The first real HYBRID LUBRICATION SYSTEM: Oil and grease from one pump

Many machines have various bearing points which have to be lubricated with grease, as well as many chains for which a lubrication with oil is necessary.

Up to now two systems were necessary for an automatic lubrication.

With the new BEKA hybrid pump system it is possible to supply **grease AND oil** with one pump at the same time.

- The innovative combination: Grease and oil from one pump
- Easy installation: Only one instead of two pumps
- Easy handling, rugged components and high efficiency





















THE COMBI SYSTEM FOR GREASE AND OIL

EPHYBRID

with electric drive

Drive: Electric motorVoltage: 12 or 24V DCReservoir sizes: 2.5 / 4.0 / 8.0 I

Outlets: 3

Operating pressure: max. 280 bar

Integrated controller

Level monitoring

Push-pull pumping element



HPHYBRID

with hydraulic drive

Drive: Hydraulic motor

Hydraulic supply: min. 6 l/min. / max. 17,2 l/min.

(equal to 1400 - 4000 min⁻¹)

Reservoir sizes: 2.5 / 4.0 / 8.0 I

Outlets: 3

Operating pressure: max. 280 bar

Push-pull pumping element



Both pumps are also available with integrated grease reservoir and external oil reservoir. Volume of the external reservoir: 2 or 4.2 l



